

6502S 65" Conference all-in-one machine

GreenTouch's 6502S 65 The series conference all-in-one machine adopts a perfect combination of the current Android operating system and X86 hardware dual operating system, integrating multiple technologies such as high-definition display, human-computer interaction, multimedia information processing, and network transmission. It can easily write, annotate, synchronize, interact with multimedia, remote video conferencing, and other applications on the conference machine, greatly improving communication efficiency in meetings, demonstrations, industry command, deployment, and other applications. It is an office and teaching platform in the information age The preferred solution for interactive demonstration with graphics and text.

Features

- Optional touch technologies include: GreenTouch infrared;
- Pluggable OPS
- Ultra-thin body
- Ultra-low standby power consumption
- One key switch
- Automatic switching of external video
- Worldwide agency approvals
- One year standard warranty

- "Designing for Touch" as the base
- Outstanding quality, reliability and Cost-effective

About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product. Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—Green-Touch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen, various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001 Quality Management System. The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation. Our products have been certified to CE, FCC, ROHS. The objective of GreenTouch is to become the most reliable supplier of touch screen, high value-added and special touch products and touch solutions in the world.

Applications

- classroom
- meeting room
- Showroom
- Command Room



Specifications

	Size	65"	
	Model	GT-TCSJHS-6502S	
Exterior	Shell material	Aluminum alloy frame, black	
	Dimensions(mm)	1426.7×112.9×88.89MM	
LCD	Screen type	65" diagonal, 1G9, Active matrix TFT LCD	
	Useful screen area(mm)	1429.3(H)×804.9(V)	
	Resolution	3840×2160@60Hz	
	Brightness (typical)	350cd/m2	
	Contrast ratio	5000:1	
	Colors	10 bit/16.7 Million	
	Viewing angle (from center)	Horizontal (left/right): 89/89° , or 178° in total; Vertical (up/down): 89/89° , or 178° in total	
Infrared touch screen parameters	Touch type	Infrared touch screen	
	Touch points	20	
	Touch drive mode	HID free drive	
	Touch screen glass	4MM tempered glass	
	Touch screen sensing method	Fingers, touch pens, or other non transparent objects with a diameter of no less than 5mm (multi point 9mm)	
	Touch screen positioning resolution	32767X32767	
	Touch system communication port	USB Touch	
	Detection function and calibration	With software automatic detection function	
	Responding speed	<15ms	
	Scan speed	60Hz/帧	
Computer host configuration	Touch accuracy	±2mm	
	Operating system	Support Win 7/8/10; Unix; android	
	Service life	Theory infinite	
	Motherboard	Optional OPS	
	Model	T982	
	System version	Android11.0	
	Processor	Quad-core ARM Cortex-A55	
	Configuration	4G+32G	
	Input port	RJ45 IN * 1, RS232 * 1, USB2.0 * 3 (including front end), USB3.0 * 2 (including front end), USB Touch * 2 (including front end), HDMI * 3 (including front end), AV IN * 1 (Mini 3-in-1)	
	Output port	Earphone Out * 1, AV OUT * 1, SPDIF OUT * 1	
Webcam	Wifi	2.4G Wi-Fi	
	Sound output power	8Ω 10W x2	
	Number of speakers	2	
	Pixel	12 million pixels	
	Number of microphones	8-microphone high-efficiency polar equidistant array microphone	
	Power supply	Voltage range	AC 200-264V 50/60Hz
		Power consumption	About 120W
		Standby power consumption	≤0.5W
		Operating temperature	-10°C - 55°C
	Surroundings	Working humidity	10% - 90%RH, No condensation
Storage temperature		-20°C - 60°C	
Storage humidity		10% - 90%RH, No condensation	
Package Size		1645x210x1025	
Package	Net weight	30kg	
	Gross weight	39kg	

Ordering Information

Part Number	Display Ports	RAM	Storage	Surface Treatment	Availability
GT-TCSJHS-6502S-T982-D4GS32G	T982	4G	32G	Clear	Worldwide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

Service call: +86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved.

2016 Shenzhen GreenTouch Technology Co., Ltd. All rights reserved.