

9803S 98" Conference all-in-one machine

GreenTouch's 98035 98 The series conference all-in-onemachine adopts a perfect combination of the currentAndroid operating system and X86 hardware dualoperating system, integrating multiple technologies such as high-definition display, human-computer interaction, multimedia information processing, and network transmission. It can easily write, annotate, synchronize, interact with multimedia, remote video conferencing, and other applications on the conference machine, greatly improving communication efficiency in meetings, demonstrations, industry command, deployment, and other applications. It is an office and teaching platform in the information age The preferred solution for interactive demonstration with graphics and text.

Features

- Optional touch technologies include: GreenTouch infrared:
- Pluggable OPS
- · Ultra-thin body
- · Ultra-low standby power consumption
- · One key switch
- · Automatic switching of external video
- · Worldwide agency approvals
- · One year standard warranty

- · "Designing for Touch" as the base
- · Outstanding quality, reliability and Cost-effective

About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product.Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—GreenTouch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen,various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001 Quality Management System . The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation.Our products have been certified to CE, FCC, ROHS . The objective of GreenTouch is to become the most reliable supplier oftouch screen, high value-added and special touch products and touch solutions in the world.

Applications

- classroom
- · meeting room
- Showroom
- · Command Room





Specifications

Size		98'			
Model		GT-TCSJHS-9803S			
	Shell material	Aluminum alloy frame, black			
Exterior	Dimensions(mm)	2221.7 × 1336.6 × 105.5MM			
	Screen type	98' diagonal, 16:9, Active matrix TFT LCD			
	Useful screen area(mm)	2160(H) x1215.7(V)			
	Resolution	3840 x 2160 @ 60Hz			
LCD	Brightness (typical)	350cd/m2			
	Contrast ratio	5000:1			
	Colors	10 bit/16.7 Million			
	Viewing angle (from center)	Horizontal (left/right): 89/89°, or 178° in total; Vertical (up/down): 89/89°, or 178° in total			
	Touch type	Infrared touch screen			
	Touch points	20			
		HID free drive			
	Touch drive mode				
	Touch screen glass	4MM tempered glass			
	Touch screen sensing method	Fingers, touch pens, or other non transparent objects with a diameter of no less than 5mm (multi point 8r			
nfrared touch screen	Touch screen positioning resolution	32767X32767			
parameters	Touch system communication port Detection function and calibration	USB Touch With software automatic detection function			
	Responding speed	with software automatic detection function <15ms			
	Scan speed	60HZ/\$9			
		S2mm			
	Touch accuracy				
	Operating system	Support Win 7/8/10; Linux; android			
d	Service life	Theory infinite			
Computer host configuration	Motherboard	Optional OPS			
	Model	T982			
	System version	Android11.0			
	Processor	Quad-core ARM Cortex-ASS			
	Configuration	4G+32G			
Standard motherboard	Input port	RJ45 IN * 1, RS232 * 1, USB2.0 * 3 (including front end), USB3.0 * 2 (including front end), USB Touch * (including front end), HDMI * 3 (including front end), AV IN * 1 (Mini 3-in-1)			
	Output port	Earphone Out*1, AV OUT *1,SPDIF OUT *1			
	Wifi	2.4G Wi-Fi			
	Sound output power	8Q 10W x2			
	Number of speakers	,			
Webcam	Pixel	12 million pixels			
Microphone	Number of microphones	8-microphone high-efficiency polar equidistant array microphone			
тисорионе	Voltage range	AC 200-264V 50/60Hz			
Power supply	Power consumption	About 400W			
rower suppry	Standby power consumption	≤0.5W			
	Standby power consumption Operating temperature	≥0.5W			
Surroundings	Working humidity	10% - 90%RH, No condensation -20°C-60°C			
	Storage temperature Storage humidity	-20 C-60 C 10% - 90%RH, No condensation			
	Package Size	2430x250x1530			
Package	Net weight	93kg			
-6-	Gross weight	119kg			

Ordering Information

Part Number	Display Ports	RAM	Storage	Surface Treatment	Availability
GT-TCSJHS-9803S-T982-D4GS32G	T982	4G	32G	Clear	Worldwide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn