



- Notes:**
1. Type: Film to Glass
  2. Operating Voltage:  $\leq 10V$
  3. Operation Temperature:  $-20^{\circ}C \sim 65^{\circ}C$   
Storage Temperature:  $-30^{\circ}C \sim 70^{\circ}C$
  4. Life Time: 1,000,000 times
  5. Connect Material: FPC
  6. Response Time:  $\leq 10ms$
  7. Linearity:  $\leq 1.5\%$
  8. Transmittance:  $\geq 75\%$
  9. Surface Hardness:  $\geq 3H$  (pencil)
  10. Operation force:  $60g \sim 150g$
  11. Resistance: X:  $360\Omega \sim 880\Omega$  Y:  $203\Omega \sim 495\Omega$

(UNLESS OTHERWISE STATED)  
TOLERANCES  
DECIMALS ANGLES 30/75%

|                 |               |              |
|-----------------|---------------|--------------|
| 1600< X< 2500MM | $\geq 20.0MM$ | $\pm 2.0MM$  |
| 1200< X< 1600MM | $\pm 1.72MM$  | $\pm 0.2MM$  |
| 800< X< 1200MM  | $\pm 0.50MM$  | $\pm 0.1MM$  |
| 400< X< 800MM   | $\pm 0.40MM$  | $\pm 0.05MM$ |
| 120< X< 400MM   | $\pm 0.25MM$  | $\pm 0.05MM$ |
| 30< X< 120MM    | $\pm 0.15MM$  | $\pm 0.05MM$ |

|            |              |                                |          |
|------------|--------------|--------------------------------|----------|
|            |              | GreenTouch Technology Co., Ltd |          |
| Model No.: | GT-4H-1214-1 | Size                           | 12.1"    |
| Structure  | GT-F         | Unit                           | mm       |
| Design     | 李松           | Date                           | 2015.5.5 |
| Check      | 441#-H       | Date                           | 2015.5.5 |
| Released   | 22#          | Date                           | 2015.5.5 |
| Scale      | Ratio        | Page                           | 4/3      |
| Version    | 1:1          | Page                           | 1/1      |
|            | NO           |                                |          |