



- Notes:
1. Type: Film to Glass
  2. Operating Voltage:  $\leq 10V$
  3. Operation Temperature:  $20^{\circ}C \sim 65^{\circ}C$   
Storage Temperature:  $-30^{\circ}C \sim 70^{\circ}C$
  4. Life Time: 1,000,000 times
  5. Connect Material: FPC
  6. Response Time:  $\leq 10ms$
  7. Linearity:  $\leq 1.5\%$
  8. Transmittance:  $\geq 75\%$
  9. Surface Hardness:  $\geq 3H$  (pencil)
  10. Operation force:  $60g \sim 150g$
  11. Resistance: X:  $152\Omega \sim 371\Omega$  Y:  $480\Omega \sim 1174\Omega$

TOLERANCES  
(UNLESS OTHERWISE STATED)

DECIMALS	ANGLES
>200MM	$\pm 2.0MM$
100- X-200MM	$\pm 1.2MM$
1200- X-5120MM	$\pm 0.50MM$
800- X-5120MM	$\pm 0.50MM$
400- X-500MM	$\pm 0.40MM$
120- X-500MM	$\pm 0.30MM$
30- X-5120MM	$\pm 0.20MM$
<30MM	$\pm 0.10MM$

		GreenTouch Technology Co., Ltd	
Model No.:	GT-4H-1804-1	Size:	13.3"
Structure:	GF+C	Unit:	mm
Design:	李强	Date:	2015.5.5
Check:	付作书	Date:	2015.5.5
Released:	汪强	Date:	2015.5.5
Version:		Scale:	1:1
		Page:	1/1
		Version:	A.0