



Logic:



CABLE 4 POSITION
HX-543 OR EQUIVALENT



DETAIL A NTS

Notes:

1. Type: Film to Film
2. Operating Voltage: $\leq 10V$
3. Operation Temperature: $-20^{\circ}C \sim 65^{\circ}C$
Storage Temperature: $-30^{\circ}C \sim 70^{\circ}C$
4. Life Time: 1,000,000 times
5. Connect Material: FPC
6. Response Time: $\leq 10ms$
7. Linearity: $\leq 1.5\%$
8. Transmittance: $\geq 75\%$
9. Surface Hardness: $\geq 3H$ (pencil)
10. Operation force: $60g \sim 150g$
11. Resistance: X: $480 \sim 1174\Omega$ Y: $152\Omega \sim 371\Omega$

<p>(UNLESS OTHERWISE STATED) DIMENSIONS ANGLES: $\pm 0.5\%$</p> <p>TOLERANCES $> 200MM$: $\pm 2.0MM$ $100 < X \leq 200MM$: $\pm 1.2MM$ $50 < X \leq 100MM$: $\pm 0.5MM$ $20 < X \leq 50MM$: $\pm 0.4MM$ $10 < X \leq 20MM$: $\pm 0.3MM$ $< 10MM$: $\pm 0.1MM$</p>		<p>Model No.: GT-4H-180A-2</p> <p>Structure: FPC</p> <p>Design: 346</p> <p>Check: 44749</p> <p>Released: 2015.7.15</p>	<p>Size: 15.6"</p> <p>Unit: mm</p> <p>Date: 2015.7.15</p> <p>Date: 2015.7.15</p> <p>Date: 2015.7.15</p>	<p>Ratio: 1:1</p> <p>Scale: 1:1</p> <p>Page: 1/1</p> <p>Version: A0</p>
<p>GreenTouch 綠觸科技</p> <p>GreenTouch Technology Co., Ltd</p>				