



- Notes:
1. Type: Film to Film
 2. Operating Voltage: $\leq 10V$
 3. Operation Temperature: $-20^{\circ}C \sim 65^{\circ}C$
Storage Temperature: $-30^{\circ}C \sim 70^{\circ}C$
 4. Life Time: 1,000,000 times
 5. Connect Material: FPC
 6. Response Time: $\leq 10ms$
 7. Linearity: $\leq 1.5\%$
 8. Transmittance: $\geq 75\%$
 9. Surface Hardness: $\geq 3H$ (pencil)
 10. Operation force: $60g \sim 150g$
 11. Resistance: X: $333\Omega - 814\Omega$ Y: $220\Omega - 536\Omega$

TOLERANCES (UNLESS OTHERWISE STATED) DECIMALS ANGLES ±0.5°		GreenTouch Technology Co., Ltd	
1800 < X ≤ 2000MM	±2.00MM	±2.00MM	
1200 < X ≤ 1800MM	±0.50MM	±0.50MM	
800 < X ≤ 1200MM	±0.30MM	±0.30MM	
400 < X ≤ 800MM	±0.40MM	±0.40MM	
120 < X ≤ 400MM	±0.30MM	±0.30MM	
30 < X ≤ 120MM	±0.20MM	±0.10MM	
< 30MM			

Model No.:	GT-4H-17A2	Size	17"	Ratio	4:3
Structure	F+T	Unit	mm	Scale	1:1
Design	张旭	Date	2015.6.5	Page	1/1
Check	张旭	Date	2015.6.5	Version	A.0
Released	张旭	Date	2015.6.5		