


CABLE 4
POSITION

HX-543 OR
EQUIVALENT



DETAIL A
NTS

- Notes:
1. Type: Film to Glass
 2. Operating Voltage: $\leq 10V$
 3. Operation Temperature: $20\text{ }^{\circ}\text{C} \sim 65\text{ }^{\circ}\text{C}$
Storage Temperature: $-30\text{ }^{\circ}\text{C} \sim 70\text{ }^{\circ}\text{C}$
 4. Life Time: 1,000,000 times
 5. Connect Material: FPC
 6. Response Time: $\leq 10\text{ms}$
 7. Linearity: $\leq 1.5\%$
 8. Transmittance: $\geq 75\%$
 9. Surface Hardness: $\geq 3H$ (pencil)
 10. Operation force: $60g \sim 150g$
 11. Resistance: X: $417\Omega - 1152\Omega$ Y: $155\Omega - 378\Omega$

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES: ±0.5%

1600- X $\leq 200\text{MM}$	±1.20MM
1200- X $\leq 1600\text{MM}$	±0.80MM
800- X $\leq 1200\text{MM}$	±0.50MM
400- X $\leq 800\text{MM}$	±0.30MM
120- X $\leq 400\text{MM}$	±0.20MM
50- X $\leq 120\text{MM}$	±0.10MM

		GreenTouch Technology Co., Ltd	
		Model No.:	GT-4W-18.5A-1
Structure	GHF	Size	18.5"
Change	变更	Unit	mm
Check	检查	Date	2015.5.5
Reviewed	审核	Date	2015.5.5
		Ratio	1:1
		Scale	1:1
		Page	1/1
		Version	A0

