


- Notes:
- 1.Type:Film to Glass
  - 2.Operating Voltage: ≤10v
  - 3.Operation Temperature: -20 °C ~ 65 °C  
Storage Temperature: -30 °C ~ 70 °C
  - 4.Life Time: 1,000,000 times
  - 5.Connect Material: FPC
  - 6.Response Time: ≤10ms
  - 7.Linearity: ≤1.5%
  - 8.Transmittance: ≥75%
  - 9.Surface Hardness ≥3H (pencil)
  - 10.Operation force: 60g ~ 150g
  - 11.Resistance: X: 480Ω-1174Ω Y: 152Ω-371Ω



TOLERANCES  
(UNLESS OTHERWISE STATED)  
DECIMALS ANGLES ±0.5%

>2000MM	±2.00MM
1800< X ≤2000MM	±1.20MM
1200< X ≤1800MM	±0.80MM
800< X ≤1200MM	±0.50MM
400< X ≤800MM	±0.40MM
120< X ≤400MM	±0.30MM
30< X ≤120MM	±0.20MM
<30MM	±0.10MM

<b>GreenTouch</b>		<b>GreenTouch Technology Co.,Ltd</b>			
Model No.:	GT-4W-18.5B-1	Size	18.5"	Ratio	16:9
Structure	G+F	Unit	mm	Scale	1:1
Design	李俊	Date	2015.8.5	Page	1/1
Check	付作书	Date	2015.8.5	Version	A0
Release	在屏	Date	2015.8.5		