



- Notes:
- 1.Type:Film to Glass
 - 2.Operating Voltage:≤10V
 - 3.Operation Temperature:-20℃~65℃
Storage Temperature:-30℃~70℃
 - 4.Life Time:1.000.000 times
 - 5.Connect Material:FPC
 - 6.Response Time:≤10ms
 - 7.Linearity:≤1.5%
 - 8.Transmittance:≥75%
 - 9.Surface Hardness≥3H(pencil)
 - 10.Operation force:60g~150g
 - 11.Resistance:X:168Ω-411Ω Y:433Ω-1059Ω

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES ±0.5%

>200MM	±2.00MM
1600< X ≤200MM	±1.20MM
1200< X ≤1600MM	±0.80MM
800< X ≤1200MM	±0.50MM
400< X ≤800MM	±0.40MM
120< X ≤400MM	±0.30MM
30< X ≤120MM	±0.20MM
<30MM	±0.10MM

		GreenTouch Technology Co.,Ltd	
		Model No.:	GT-4W-19B-1
Structure	G+F	Size	19"
Design	李俊	Unit	mm
Check	付作书	Date	2020.04.22
Release	汪陈	Date	2020.04.22
		Ratio	16:10
		Scale	1:1
		Page	1/1
		Version	A0