



- Notes:
1. Type: Film to Film
 2. Operating Voltage: $\leq 10V$
 3. Operation Temperature: $-20^{\circ}C \sim 65^{\circ}C$
Storage Temperature: $-30^{\circ}C \sim 70^{\circ}C$
 4. Life Time: 1,000,000 times
 5. Connect Material: FPC
 6. Response Time: $\leq 10ms$
 7. Linearity: $\leq 1.5\%$
 8. Transmittance: $\geq 75\%$
 9. Surface Hardness: $\geq 3H$ (pencil)
 10. Operation force: $60g \sim 150g$
 11. Resistance: X: $433\Omega - 1059\Omega$ Y: $168\Omega - 411\Omega$

TOLERANCES (UNLESS OTHERWISE STATED) DECIMALS ANGLES ±0.5°		GreenTouch Technology Co., Ltd	
1800 < X ≤ 2000MM	±1.20MM	Model No.:	GT-4H-18B-2
2000 < X ≤ 2500MM	±2.00MM	Structure:	F+T
2500 < X ≤ 3000MM	±2.50MM	Design:	3H
3000 < X ≤ 3500MM	±3.00MM	Check:	4H/5H
3500 < X ≤ 4000MM	±3.50MM	Released:	日期
4000 < X ≤ 4500MM	±4.00MM		
4500 < X ≤ 5000MM	±4.50MM		
5000 < X ≤ 5500MM	±5.00MM		
5500 < X ≤ 6000MM	±5.50MM		
6000 < X ≤ 6500MM	±6.00MM		
6500 < X ≤ 7000MM	±6.50MM		
7000 < X ≤ 7500MM	±7.00MM		
7500 < X ≤ 8000MM	±7.50MM		
8000 < X ≤ 8500MM	±8.00MM		
8500 < X ≤ 9000MM	±8.50MM		
9000 < X ≤ 9500MM	±9.00MM		
9500 < X ≤ 10000MM	±9.50MM		
> 10000MM	±10.00MM		

Model No.:	Size	Ratio
GT-4H-18B-2	19"	16:9

Structure:	Unit	Scale
F+T	mm	1:1

Design:	Date	Page
3H	2015.10.5	1/1

Check:	Date	Version
4H/5H	2015.10.5	A.0

Released:	Date
日期	2015.10.5