



- Notes:
1. Type: Film to Glass
  2. Operating Voltage:  $\leq 10V$
  3. Operation Temperature:  $20^{\circ}C \sim 65^{\circ}C$   
Storage Temperature:  $-30^{\circ}C \sim 70^{\circ}C$
  4. Life Time: 1,000,000 times
  5. Connect Material: FPC
  6. Response Time:  $\leq 10ms$
  7. Linearity:  $\leq 1.5\%$
  8. Transmittance:  $\geq 75\%$
  9. Surface Hardness:  $\geq 3H$  (pencil)
  10. Operation force:  $60g \sim 150g$
  11. Resistance: X:  $483\Omega$ - $1181\Omega$  Y:  $151\Omega$ - $369\Omega$

TOLERANCES (UNLESS OTHERWISE STATED) DIMENSIONS ANGLES .05mm		GreenTouch Technology Co., Ltd	
1000-X-6500MM	$\pm 2.00MM$	Model No.:	GT-483-181D
1200-X-8100MM	$\pm 2.00MM$	Quantity:	21.5"
800-X-8100MM	$\pm 0.20MM$	Color:	White
400-X-800MM	$\pm 0.40MM$	Display:	2200 2018.7.5
1200-X-4000MM	$\pm 0.20MM$	Client:	2200 2018.7.5
800-X-8100MM	$\pm 0.20MM$	Version:	2018.7.5
300-X-8100MM	$\pm 0.10MM$	Rev:	1.0