



- Notes:**
1. Type: Film to Glass
  2. Operating Voltage:  $\leq 10V$
  3. Operation Temperature:  $20^{\circ}C \sim 65^{\circ}C$   
Storage Temperature:  $-30^{\circ}C \sim 70^{\circ}C$
  4. Life Time: 1,000,000 times
  5. Connect Material: FPC
  6. Response Time:  $\leq 10ms$
  7. Linearity:  $\leq 1.5\%$
  8. Transmittance:  $\geq 75\%$
  9. Surface Hardness:  $\geq 3H$  (pencil)
  10. Operation force: 60g ~ 150g
  11. Resistance: X:  $450\Omega - 1100\Omega$  Y:  $163\Omega - 400\Omega$

TOLERANCES  
(UNLESS OTHERWISE STATED)

DECIMALS	ANGLES	$\pm 0.5\%$
$> 2000MM$	$\pm 2.00MM$	
$1600 < X \leq 2000MM$	$\pm 1.20MM$	
$1200 < X \leq 1600MM$	$\pm 0.80MM$	
$800 < X \leq 1200MM$	$\pm 0.50MM$	
$400 < X \leq 800MM$	$\pm 0.30MM$	
$120 < X \leq 400MM$	$\pm 0.20MM$	
$30 < X \leq 120MM$	$\pm 0.10MM$	
$< 30MM$		

<b>GreenTouch</b>		GreenTouch Technology Co., Ltd	
Model No.:	GT-AW-Z2A-1	Size	22"
Structure	GF-F	Unit	mm
Design	李俊	Date	2015.7.22
Check	符作非	Date	2015.7.22
Release	汪燕	Date	2015.7.22
Ratio	16:10	Scale	1:1
Page	1/1	Version	AO