



- Instruction:**
1. Typo: Film to Glass
 2. Operating Voltage: 10V
 3. Response Time: 10ms
 4. Storage Temperature: -20°C ~ +70°C
 5. Operation Temperature/Humidity: -10°C ~ +60°C / 20% ~ 85%
 6. Holding Life: >10,000,000 Times 250g Force
 7. Writing Life: >1,000,000 Times 250g Force
 8. Contact Material: FPC
 9. Film Thickness: 188um
 10. Glass Thickness: 1.1mm
 11. Light Transmittance: >75%
 12. Force: 100g or more
 13. Linearity: <5%
 14. Resolution: 250x120
 15. Resistance: 30Ω < PIN1, PIN2 < 250Ω
80Ω < PIN3, PIN4 < 250Ω
80Ω < PIN5, PIN6 < 250Ω
 16. Surface Hardness: 3H (penal)

TOLERANCES
(UNLESS OTHERWISE STATED)
DIMENSIONS AND ANGLES IN MM

>2000MM	±2.00MM
1800 ~ X 6000MM	±1.50MM
1200 ~ X 6150MM	±1.00MM
400 ~ X 600MM	±0.50MM
120 ~ X 600MM	±0.30MM
30 ~ X 615MM	±0.10MM

GreenTouch Technology Co., Ltd

Model No.:	GT-091-7M-1	Size	7"™	Ratio	99%
Structure	GF	Unit	mm	Grade	1:1
Design	4H	Date	2014.11.15	Page	1/1
Client	4H	Date	2014.11.15	Version	A0
Revision	001	Date	2014.11.15		