



Front ITO Film-0.188mm

Back ITO Glass-1.8mm

- Notes:
- 1.Type:Film to Glass
  - 2.Operating Voltage:≤10v
  - 3.Operation Temperature:-20℃~65℃  
Storage Temperature:-30℃~70℃
  - 4.Life Time:1.000.000 times
  - 5.Connect Material:FPC
  - 6.Response Time:≤10ms
  - 7.Linearity:≤1.5%
  - 8.Transmittance:≥75%
  - 9.Surface Hardness≥3H(pencil)
  - 10.Operation force:60g~150g

- 11.Resistance:50Ω < PIN1,PIN2 < 250Ω  
50Ω < PIN2,PIN4 < 250Ω  
50Ω < PIN4,PIN5 < 250Ω  
50Ω < PIN5,PIN1 < 250Ω

TOLERANCES  
(UNLESS OTHERWISE STATED)

DECIMALS	ANGLES	±0.5%
>2000MM	±2.00MM	
1600< X ≤2000MM	±1.20MM	
1200< X ≤1600MM	±0.80MM	
800< X ≤1200MM	±0.50MM	
400< X ≤800MM	±0.40MM	
120< X ≤400MM	±0.30MM	
30< X ≤120MM	±0.20MM	
<30MM	±0.10MM	



GreenTouch Technology Co.,Ltd

Model No.:	GT-5W-121A-1	Size	12.1"	Ratio	4:3
Structure	G+F	Unit	mm	Scale	1:1
Design	李俊	Date	2020.3.20	Page	1/1
Check	付作韦	Date	2020.3.20	Version	A0
Release	汪陈	Date	2020.3.20		