



Front ITO Film-0.188mm  
Back ITO Glass-1.8mm

Thick: 2.3 ± 0.15

- Notes:
1. Typical to Glass
  2. Operating Voltage: <math>\le 10V</math>
  3. Operating Temperature: <math>20^{\circ}C \sim 60^{\circ}C</math>
  4. Storage Temperature: <math>30^{\circ}C \sim 70^{\circ}C</math>
  - 4.1 Life Time: 1,000,000 times
  5. Current Material: FPC
  6. Response Time: <math>\le 18ms</math>
  7. Lifetime: <math>\le 1.25%</math>
  8. Transmittance: <math>\ge 70%</math>
  9. Surface Hardness: <math>\ge 4H</math>
  10. Operation Frequency: <math>\sim 150g</math>

11. Resistance: 50Ω <math>< P\_{IN1}, P\_{IN2}</math> <math>< 250Ω</math>  
 50Ω <math>< P\_{IN2}, P\_{IN4}</math> <math>< 250Ω</math>  
 50Ω <math>< P\_{IN4}, P\_{IN5}</math> <math>< 250Ω</math>  
 50Ω <math>< P\_{IN5}, P\_{IN1}</math> <math>< 250Ω</math>

TOURNAIRES  
QUALITE OUVRIERE SVTED  
DIPLOME AVEUE 4878  
> 2000000

4000-X-4500MM	51.500MM
4200-X-4500MM	50.000MM
4500-X-4500MM	50.000MM
4800-X-4500MM	50.000MM
5100-X-4500MM	50.000MM
5400-X-4500MM	50.000MM

GreenTouch® GreenTouch Technology Co., Ltd

Model No.	GT-001-01A-06	Size	12"	Color	4.3
Material	50T	Lot	001	Part	51
Version	01/13	Date	2013/08/15	Page	1/1
Drawn	01/13	Check	2013/08/15	Version	01
Checked	01/13	Drawn	2013/08/15	Checked	01