



Front ITO Film-0.188mm
Back ITO Glass-1.8mm

Thick: 2.3±0.15

Notes:

- 1.Type: Film to Glass
- 2.Operating Voltage: ≤10v
- 3.Operating Temperature: -20℃~65℃
Storage Temperature: -30℃~70℃
- 4.Life Time: 1,000,000 times
- 5.Connect Material: FPC
- 6.Response Time: <10ms
- 7.Linearity: ≤1.5%
- 8.Transmittance: >75%
- 9.Surface Hardness: 3H(pencil)
- 10.Operation force: 90g~180g

- 11.Resistance: 90Ω < PIN1, PIN2 < 250Ω
80Ω < PIN3, PIN4 < 250Ω
80Ω < PIN4, PIN5 < 250Ω
90Ω < PIN5, PIN1 < 250Ω

TOLERANCE	(UNLESS OTHERWISE STATED)
DECIMALS	ANGLES ±0.5°
>30.0MM	±0.20MM
10.0 - < 30.0MM	±0.15MM
3.00 - < 10.00MM	±0.10MM
0.50 - < 3.00MM	±0.05MM
0.25 - < 0.50MM	±0.02MM
0.10 - < 0.25MM	±0.01MM
<0.10MM	±0.005MM



GreenTouch Technology Co., Ltd

Model No.:	GT-09-15D-1	Size	15"	Part	4-9
Structure	④F	Unit	mm	Scale	1:1
Design	④R	Date	2016.02	Page	1/1
Check	④P-S	Date	2016.02	Version	A0
Release	④R	Date	2016.02		