



- Notes:
1. Type Film to Glass
 2. Operating Voltages: ≤10V
 3. Operation Temperature: 20°C ~ 65°C
 4. Storage Temperature: -30°C ~ 70°C
 5. All life Time: 1,000,000 times
 6. Curved Material: FPC
 7. Response Time: ≤10ms
 8. Linearity: ≤1.5%
 9. Transmittance: ≥75%
 10. Surface Hardness: ≥3H (pencil)
 11. Operation force: 50g ~ 150g

Front ITO Film-0.188mm
 Back ITO Glass-1.8mm
 Thickness: 2.3 ± 0.15

11. Resistance: 50Ω < PIN1, PIN2 < 250Ω
 50Ω < PIN2, PIN3 < 250Ω
 50Ω < PIN4, PIN5 < 250Ω
 50Ω < PIN5, PIN1 < 250Ω

TOLERANCES
 (UNLESS OTHERWISE STATED)
 DECIMALS ANGLES ±0.5%

>200.0MM	±2.0MM
100.0 - X < 200.0MM	±1.2MM
50.0 - X < 100.0MM	±0.50MM
25.0 - X < 50.0MM	±0.25MM
<25.0MM	±0.10MM

Model No.	QT-20V-10E-1	Size	15"	Ratio	4:3
Structure	QUT	Unit	mm	Scale	1:1
Design	张旭	Date	2015.3.2	Page	1/1
Check	张旭	Date	2015.3.2	Version	00
Revision	张旭	Date	2015.3.2		

GreenTouch Technology Co., Ltd