



PIN #	Assignment
1	LB
2	LT
3	S
4	RB
5	RT

- Notes:
- Type: Film to Glass
 - Operating Voltage: 510V
 - Operating Temperature: 20°C ~ 85°C
 - Storage Temperature: 30°C ~ 70°C
 - Life Time: 1,000,000 times
 - Connect Material: FPC
 - Response Time: 510ms
 - Linearity: $\leq 1.5\%$
 - Transmittance: $\geq 75\%$
 - Surface Hardness: $\geq 3H$ (pencil)
 - Operation Force: 80g ~ 150g

11. Resistance: 50Ω < PIN1, PIN2 < 250Ω
 50Ω < PIN2, PIN4 < 250Ω
 50Ω < PIN4, PIN5 < 250Ω
 50Ω < PIN5, PIN1 < 250Ω

GreenTouch 綠域觸控

GreenTouch Technology Co., Ltd

TOLERANCES (UNLESS OTHERWISE STATED)	
DESCRIPTORS : ANGLES	±0.5°
>200MM	±2.00MM
1600- X- 5200MM	±1.20MM
1200- X- 5160MM	±0.80MM
800- X- 5120MM	±0.50MM
400- X- 5800MM	±0.40MM
120- X- 5400MM	±0.20MM
30- X- 5120MM	±0.10MM

Model No.:	GT-0W-150-1	Size	15"	Ratio	4:3
Structure	GT-F	Unit	mm	Scale	1:1
Design	9/8	Date	2015.5	Page	1/1
Check	4/15/15	Date	2015.5	Version	A/0
Release	EEB	Date	2015.5		