



- Notes:
- 1.Type: Film to Glass
 - 2.Operating Voltage: $\leq 10V$
 - 3.Operating Temperature: $-20^{\circ}C \sim 65^{\circ}C$
 - 4.Life: 1,000,000 times
 - 5.Connect Material: ITO
 - 6.Response Time: $\leq 10ms$
 - 7.Linearity: $\leq 1.5\%$
 - 8.Transmittance: $\geq 75\%$
 - 9.Surface Hardness: $\geq 3H$ (pencil)
 - 10.Operation force: $50g \sim 150g$

11. Resistances:
- 50Ω < PIN1, PIN2 < 250Ω
 - 50Ω < PIN3, PIN4 < 250Ω
 - 50Ω < PIN5, PIN6 < 250Ω

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES 40.9%

1600 X 5120MM	±1.50MM
1200 X 5120MM	±0.50MM
800 X 5120MM	±0.50MM
400 X 5120MM	±0.50MM
300 X 5120MM	±0.50MM
<300MM	±0.10MM

GreenTouch Technology Co., Ltd

Model No.:	GT-SM-16-1	Size:	15"	Ratio:	4:3
Structure:	GT-F	Unit:	mm	Scale:	1:1
Design:	张俊	Date:	2016.7.20	Page:	1/1
Check:	张俊	Date:	2016.7.20	Version:	1.0
Released:	张俊	Date:	2016.7.20		