



- Notes:
- 1.Type: Film to Glass
 - 2.Operating Voltage: $\le 10V$
 - 3.Operating Temperature: $20^{\circ}C \sim 65^{\circ}C$
- Storage Temperature: $30^{\circ}C \sim 70^{\circ}C$
- 4.Life Time: 1,000,000 times
 - 5.Connected Material: PC
 - 6.Response Time: $\le 10ms$
 - 7.Leakage: $\le 1.5\%$
 - 8.Transmittance: $\ge 75\%$
 - 9.Surface Hardness: $\ge 3H$ (penical)
 10. Operation force: $60g \sim 150g$

11. Resistances: <math>500 < \text{PIN1, PIN2} < 2500</math>
<math>500 < \text{PIN2, PIN4} < 2500</math>
<math>500 < \text{PIN4, PIN5} < 2500</math>
<math>500 < \text{PIN5, PIN1} < 2500</math>

TOLERANCES
(UNLESS OTHERWISE STATED)
DIMENSIONS ANGLES 0.05%

1600- X $\le 200MM$	$\pm 0.2MM$
1200- X $\le 160MM$	$\pm 0.1MM$
800- X $\le 120MM$	$\pm 0.05MM$
400- X $\le 60MM$	$\pm 0.02MM$
30- X $\le 12MM$	$\pm 0.10MM$

		GreenTouch Technology Co., Ltd	
		Model No.:	GT-SH-15.6C-1
Structure	GH	Size	15.6"
Design	FR	Unit	mm
Check	HT	Date	2016.8.3
Released	ES	Date	2016.8.3
		Scale	1:1
		Page	1/1
		Version	1.0