



Front ITO Film-0.188mm
 Back ITO Glass-1.8mm
 Thick: 2.3 ± 0.15

- Notes:
1. Type: Film to Glass
 2. Operating Voltage: 510V
 3. Operating Temperature: 20°C ~ 65°C
 4. Life Time: 1,000,000 times
 5. Storage Temperature: 30°C ~ 70°C
 6. Connect Material: FPC
 7. Response Time: 5 (10ms)
 8. Linearity: ±1.5%
 9. Transmittance: ≥75%
 10. Operation Force: 90g ~ 150g

11. Resistance: 50Ω < PIN1, PIN2 < 250Ω
 50Ω < PIN2, PIN4 < 250Ω
 50Ω < PIN4, PIN5 < 250Ω
 50Ω < PIN5, PIN1 < 250Ω

TOLERANCES (UNLESS OTHERWISE STATED) DECIMALS ANGLES 10.0%		Model No.:		Size	Ratio
1600- X < 5200MM	> 20.0MM	±1.50MM	GT-17A-1	17"	4:3
1200- X < 5160MM	> 20.0MM	±0.50MM	Structure	mm	1:1
800- X < 5120MM	> 20.0MM	±0.50MM	Design	2018.1.5	1/1
400- X < 5080MM	> 20.0MM	±0.50MM	Check	2018.1.5	1/1
120- X < 5040MM	> 20.0MM	±0.50MM	Review	2018.1.5	1/1
30- X < 5120MM	> 20.0MM	±0.50MM			

GreenTouch 綠域科技
 Green Touch Technology Co., Ltd