



Notes:

- 1.Type:Film to Glass
- 2.Operating Voltage:$\le 10v$
- 3.Operating Temperature:$20^{\circ}C \sim 65^{\circ}C$
- 4.Life Time:1,000,000 times
- 5.Connect Material:FPC
- 6.Response Time:$\le 10ms$
- 7.Linearity:$\le 1.5\%$
- 8.Transmittance:>75%
- 9.Surface Hardness:>3H(pencil)
- 10.Operation force:50g~150g

- 11.Resistance:<math>50\Omega < PIN1, PIN2 < 250\Omega</math>
<math>50\Omega < PIN2, PIN4 < 250\Omega</math>
<math>50\Omega < PIN4, PIN5 < 250\Omega</math>
<math>50\Omega < PIN5, PIN1 < 250\Omega</math>

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES ±0.05°

>300MM	±2.0MM
1500- X $\le 300MM$	±1.20MM
1200- X $\le 1500MM$	±0.80MM
800- X $\le 1200MM$	±0.50MM
400- X $\le 800MM$	±0.40MM
120- X $\le 400MM$	±0.30MM
30- X $\le 120MM$	±0.20MM
$\le 30MM$	±0.10MM

绿触科技 GreenTouch		GreenTouch Technology Co.,Ltd	
Model No.:	GT-SW-17.00-0	Size	17"
Structure	④+F	Unit	mm
Design	李强	Date	2010.05.08
Check	李伟军	Date	2010.05.08
Release	王强	Date	2010.05.08
Ratio	4:3	Scale	1:1
Page	1/1	Version	A0