



- Notes:
- 1.Type:Film to Glass
 - 2.Operating Voltage:≤10V
 - 3.Operating Temperature:20℃~70℃
 - 4.Life Time:1,000,000 times
 - 5.Connected Material:PC
 - 6.Response Time:≤50ms
 - 7.Linearity:≤1.5%
 - 8.Termination:≥75%
 - 9.Surface Hardness:≥3H(panc)
 - 10.Operation Force:80g~150g

- 11.Resistance:50Ω < PIN1, PIN2 < 250Ω
 50Ω < PIN2, PIN4 < 250Ω
 50Ω < PIN4, PIN5 < 250Ω
 50Ω < PIN5, PIN1 < 250Ω

Front ITO Film-0.188mm
 Back ITO Glass-1.8mm

TOLERANCES
 (UNLESS OTHERWISE STATED)
 DECIMALS ANGLES 0.05%

1800- >2000MM	±0.20MM
1200- <1800MM	±0.15MM
800- <1200MM	±0.10MM
400- <800MM	±0.05MM
130- <400MM	±0.02MM
30- <130MM	±0.10MM

		GreenTouch Technology Co., Ltd	
		Model No.	GT-09-19D-1
Structure	OUT	Size	19"
Design	WER	Unit	mm
Check	07/15	Date	2016.11.10
Release	EEB	Drawn	2016.11.10
		Scale	Ratio
		Drawn	1:1
		Check	YH
		Version	02