



Notes:

- 1.Type:Film to Glass
- 2.Operating Voltage:≤10v
- 3.Operation Temperature:-20°C~65°C
Storage Temperature:-30°C~70°C
- 4.Life Time:1,000,000 times
- 5.Connect Material:FPC
- 6.Response Time:≤10ms
- 7.Linearity:≤1.5%
- 8.Transmittance:≥75%
- 9.Surface Hardness≥3H(pencil)
- 10.Operation force:80g~150g

- 11.Insulation:≥20MΩ
- 12.Resistance:50Ω < PIN1,PIN2 < 250Ω
50Ω < PIN2,PIN4 < 250Ω
50Ω < PIN4,PIN5 < 250Ω
50Ω < PIN5,PIN1 < 250Ω

TOLERANCES (UNLESS OTHERWISE STATED) DECIMALS ANGLES 100%	
>2000MM	±2.00MM
600~ X ≤2000MM	±1.28MM
1200~ X ≤1600MM	±0.80MM
600~ X ≤1200MM	±0.50MM
400~ X ≤600MM	±0.40MM
120~ X ≤400MM	±0.30MM
30~ X ≤120MM	±0.20MM
<30MM	±0.10MM

GreenTouch Technology Co.,Ltd		21.5"		Ratio	W:H
Model No:	GT-SW-2104-V1	Size	21.5"	Ratio	W:H
Structure	G+P	Unit	mm	Scale	1:1
Design	SH	Date	2015.03	Page	1/1
Check	WFB	Date	2015.03	Version	A0
Release	SE	Date	2015.03		