



- Notes:
- 1.Type:Film to Glass
 - 2.Operating Voltage:≤10V
 - 3.Operating Temperature:-20°C~+65°C
 - 4.Life Time:1,000,000 times
 - 5.Connect Material:PC
 - 6.Response Time:≤10ms
 - 7.Linearity:±1.5%
 - 8.Transmittance:≥75%
 - 9.Surface Hardness:3H(pencil)
 - 10.Operation force:60g~150g

- 11.Resistances:50Ω < PIN1, PIN2 < 250Ω
50Ω < PIN2, PIN4 < 250Ω
50Ω < PIN4, PIN5 < 250Ω
50Ω < PIN5, PIN1 < 250Ω

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS: ANGLES: 40UM

>200MM	±2.00MM
100~200	±1.20MM
50~100	±0.80MM
20~50	±0.40MM
10~20	±0.20MM
<10	±0.10MM

		GreenTouch Technology Co., Ltd	
Model No.:	GT-SV-22A-1	Size	22" 11
Structure	GT	Unit	mm
Design	#12	Date	2018.2.25
Check	#17	Date	2018.2.25
Release	EEB	Date	2018.2.25
Scale	16:10	Scale	1:1
Page	1/1	Version	A0