



Front ITO Film-0.188mm  
 Back ITO Glass-1.8mm  
 Thick: 2.3 ± 0.15  
 3.0

**Notes:**

- 1.Type:Film to Glass
- 2.Operating Voltage:≤10V
- 3.Operation Temperature:-20℃~65℃  
Storage Temperature:-30℃~70℃
- 4.Life Time:1,000,000 times
- 5.Connect Material:FPC
- 6.Response Time:≤10ms
- 7.Linearity:≤1.5%
- 8.Transmittance:≥75%
- 9.Surface Hardness:≥3H(pencil)
- 10.Operation force:60g~150g

- 11.Resistance:50Ω < PIN1,PIN2 < 250Ω  
50Ω < PIN2,PIN4 < 250Ω  
50Ω < PIN4,PIN5 < 250Ω  
50Ω < PIN5,PIN1 < 250Ω

**TOLERANCES**  
(UNLESS OTHERWISE STATED)  
DECIMALS ANGLES ±0.5%

>2000MM	±2.00MM
1600< X ≤2000MM	±1.20MM
1200< X ≤1600MM	±0.80MM
800< X ≤1200MM	±0.50MM
400< X ≤800MM	±0.40MM
120< X ≤400MM	±0.30MM
30< X ≤120MM	±0.20MM
<30MM	±0.10MM

<b>格林触控</b> <b>GreenTouch</b>		<b>GreenTouch Technology Co.,Ltd</b>			
Model No.:	GT-SW-228-1	Size	22"	Ratio	16:10
Structure	G+F	Unit	mm	Scale	1:1
Design	李俊	Date	2016.8.29	Page	1/1
Check	何存书	Date	2016.8.29	Version	A0
Release	汪露	Date	2016.8.29	⊕	